



GSI WASH PIPE SIZES & SPECIFICATIONS

GSI FLUSH JOINT CONNECTION

NOMINAL SIZE (IN)	PIPE WEIGHT (LB/FT)	PIPE DIMENSIONS OD (IN)	PIPE DIMENSIONS ID (IN)	DRIFT (IN)	PIPE GRADE	MINIMUM WALL THICKNESS (IN)	OPTIMUM MUT (FT-LBS)	TENSILE YIELD (LBS)	MINIMUM MAKE-UP (FT-LBS)	OPTIMUM MAKE-UP (FT-LBS)	MAXIMUM MAKE UP (FT-LBS)
1	2.25	1.315	0.957	0.863	P-110	0.143	275	30,600	250	275	300
1 1/4	3.02	1.66	1.278	1.184	P-110	0.153	300	55,300	280	300	325
1 1/2	3.64	1.9	1.5	1.406	P-110	0.16	400	60,000	350	400	450
2 1/16	4.5	2.063	1.613	1.519	P-110	0.18	500	55,500	450	500	550
2 3/8	4.6	2.375	1.995	1.901	P-110	0.152	675	62,000	600	675	750
2 7/8	6.4	2.875	2.441	2.347	P-110	0.174	900	84,000	800	900	1000
3 1/2	9.3	3.5	2.992	2.867	P-110	0.203			1400	1600	1800
4	11.6	4	3.428	3.303	P-110	0.229			1700	1900	2100

HYDRIL 511 CONNECTION

NOMINAL SIZE (IN)	WEIGHT (LB/FT)	PIPE DIMENSIONS OD (IN)	PIPE DIMENSIONS ID (IN)	DRIFT (IN)	PIPE GRADE	MINIMUM WALL THICKNESS (IN)	OPTIMUM MUT (FT-LBS)	TENSILE YIELD (LBS)	MINIMUM MAKE-UP (LBS)	OPTIMUM MAKE-UP (LBS)	MAXIMUM MAKE UP (LBS)
2 1/6	4.5	2.063	1.613	1.519	P-110	0.18	700	87,000	600	700	1,100
2 3/8	4.6	2.375	1.995	1.901	P-110	0.152	700	85,813	550	700	1,000
2 7/8	6.4	2.875	2.441	2.347	P-110	0.174	800	109,416	700	800	1,200
3 1/2	9.2	3.5	2.992	2.867	P-110	0.203	1,700	173,500	1,400	1,700	2,500
4	11.6	4	3.428	3.303	P-110	0.229	2,400	223,930	2,000	2,400	3,500
4 1/2	12.6	4.5	3.958	3.833	P-110	0.217	2,400	230,470	2,000	2,400	3,500



info@gulfstreamservices.com



985.868.0303



gulfstreamservices.com